

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claim 1 (canceled)

1 Claim 2 (currently amended): An apparatus ~~for processing a~~
2 ~~block of data representing at least one symbol~~, the
3 apparatus comprising:
4 a Fourier transform circuit for performing at least
5 one Fourier transform on a signal used to communicate a
6 block of data representing at least one symbol;
7 a buffer coupled to said Fourier transform circuit for
8 buffering data produced from an output of said Fourier
9 transform circuit;
10 a jitter compensation filter coupled to said buffer
11 for performing a filtering operation on data obtained from
12 said buffer corresponding to said block of data to generate
13 a filtered block of data, the jitter compensation filter
14 having an update input for receiving a filter coefficient
15 update signal;
16 an error calculation module coupled to the update
17 input of the jitter compensation filter, the error
18 compensation module generating the filter coefficient
19 update signal from at least one signal error estimate made
20 from the filtered block of data output by the jitter
21 compensation filter; and
22 a control circuit coupled to said error
23 calculation module for determining as a function of said at
24 least one signal error estimate, when to output said
25 filtered block of data.

1 Claim 3 (currently amended): The apparatus of claim 2,
2 further comprising:
3 a channel compensation circuit for receiving said
4 block of data and performing a channel compensation
5 operation on at least a portion of said block of data prior
6 to the block of data being stored in said buffer for
7 processing ~~processed~~ by said jitter compensation filter.

1 Claim 4 (original): The apparatus of claim 3, wherein said
2 block of data represents a plurality of symbols, the
3 apparatus further comprising:
4 demodulator circuitry coupled to an output of the
5 jitter compensation filter.

1 Claim 5 (previously presented): The apparatus of claim 2,
2 wherein the error calculation module includes:
3 means for generating a decision directed error
4 value.

1 Claim 6 (currently amended): ~~An apparatus for processing a~~
2 ~~block of data representing at least one symbol, the~~
3 ~~apparatus comprising:~~
4 a Fourier transform circuit for performing at least
5 one Fourier transform on a signal used to communicate a
6 block of data representing at least one symbol;
7 a buffer coupled to said Fourier transform circuit for
8 buffering data produced from an output of said Fourier
9 transform circuit;
10 a jitter compensation filter coupled to said buffer
11 for performing a filtering operation on data obtained from
12 said buffer corresponding to said block of data to generate
13 a filtered block of data, the jitter compensation filter

14 having an update input for receiving a filter coefficient
15 update signal; and
16 an error calculation module coupled to the update
17 input of the jitter compensation filter, the error
18 compensation module generating the filter coefficient
19 update signal from at least one signal error estimate made
20 from the filtered block of data output by the jitter
21 compensation filter, wherein the error calculation module
22 includes:
23 means for generating a decision directed
24 error value;
25 means for generating a pilot directed error
26 value; and
27 a selection device for selecting one of the
28 decision directed error value and the pilot
29 directed error value to be output.

1 Claim 7 (currently amended): An apparatus ~~for processing a~~
2 ~~block of data representing at least one symbol~~, the
3 apparatus comprising:
4 a Fourier transform circuit for performing at least
5 one Fourier transform on a signal used to communicate a
6 block of data representing at least one symbol;
7 a buffer coupled to said Fourier transform circuit for
8 buffering data produced from an output of said Fourier
9 transform circuit;
10 a jitter compensation filter coupled to said buffer
11 for performing a filtering operation on data obtained from
12 said buffer corresponding to said block of data to generate
13 a filtered block of data, the jitter compensation filter
14 having an update input for receiving a filter coefficient
15 update signal; and

16 an error calculation module coupled to the update
17 input of the jitter compensation filter, the error
18 compensation module generating the filter coefficient
19 update signal from at least one signal error estimate made
20 from the filtered block of data output by the jitter
21 compensation filter, wherein the error calculation module
22 includes:
23 means for generating a decision directed
24 error value;
25 means for generating a non-decision directed
26 error value; and
27 a selection device for selecting one of the
28 decision directed error value and the non-
29 decision directed error value to be output.

1 Claim 8 (previously presented): The apparatus of claim 7,
2 further comprising:
3 an input buffer coupled to the jitter
4 compensation filter for storing said block of data while it
5 being processed multiple times by said jitter compensation
6 filter.

Claims 9 and 10 (canceled)

1 Claim 11 (currently amended): An apparatus ~~for processing~~
2 ~~a block of data representing at least one symbol~~, the
3 apparatus comprising:
4 a Fourier transform circuit for performing at least
5 one Fourier transform on a signal used to communicate a
6 block of data representing at least one symbol;

7 a buffer coupled to said Fourier transform circuit for
8 buffering data produced from an output of said Fourier
9 transform circuit;
10 a jitter compensation filter coupled to said buffer
11 for performing a filtering operation on data obtained from
12 said buffer corresponding to said block of data to generate
13 a filtered block of data, the jitter compensation filter
14 having an update input for receiving a filter coefficient
15 update signal, said buffer storing said block of data while
16 said block of data is processed multiple times by said
17 jitter compensation filter;
18 an error calculation module coupled to the update
19 input of the jitter compensation filter, the error
20 compensation module generating the filter coefficient
21 update signal from at least one signal error estimate made
22 from the filtered block of data output by the jitter
23 compensation filter;
24 ~~an input buffer for storing said block of data while~~
25 ~~being processed multiple times by said jitter compensation~~
26 ~~filter; and~~
27 an output control device for determining when to
28 output the filtered block of data generated by said jitter
29 compensation filter.

1 Claim 12 (original): The apparatus of claim 11, wherein
2 the output control device includes:
3 means for determining when said block of data has been
4 filtered a fixed number of times by the jitter compensation
5 filter.

1 Claim 13 (original): The apparatus of claim 11,

2 wherein the output control device includes an input
3 for receiving the filter coefficient update signal
4 generated by said error calculation module; and
5 wherein the jitter compensation filter further
6 includes means for resetting filter coefficient values to a
7 set of initial values in response to a reset signal
8 generated by said output control device.

Claims 14 and 15 (canceled)

1 Claim 16 (currently amended): A system for processing a
2 multi-tone signal, the system including:
3 a Fourier transform circuit for performing at least
4 one Fourier transform on said multi-tone signal;
5 a channel compensation module coupled to said Fourier
6 transform circuit for performing a channel compensation
7 operation on said multi-tone signal after processing by
8 said Fourier transform circuit;
9 a buffer coupled to said Fourier transform circuit for
10 buffering the channel compensated multi-tone signal;
11 a jitter compensation module coupled to an output of
12 the channel compensation module said buffer for performing
13 a jitter reduction operation on the buffered channel
14 compensated multi-tone signal, wherein the jitter
15 compensation module includes : a jitter compensation filter
16 with programmable filter tap weights, and means for
17 iteratively updating the filter tap weights as a function
18 of the jitter compensation filter output; and
19 a control circuit for determining when the output of
20 the jitter compensation filter should be used as the output
21 of the jitter compensation module.

1 Claim 17 (previously presented): The system of claim 16,
2 wherein the means for iteratively updating the filter tap
3 weights includes:
4 a signal error estimation circuit for generating from
5 the output of the jitter compensation filter a measure of a
6 symbol error.

1 Claim 18 (currently amended): A system for processing a
2 multi-tone signal, the system including:
3 a Fourier transform circuit for performing at least
4 one Fourier transform on said multi-tone signal;
5 a channel compensation module coupled to said Fourier
6 transform circuit for performing a channel compensation
7 operation on said multi-tone signal after processing by
8 said Fourier transform circuit;
9 a buffer coupled to said Fourier transform circuit for
10 buffering the channel compensated multi-tone signal;
11 a jitter compensation module coupled to said buffer on
12 output of the channel compensation module for performing a
13 jitter reduction operation on the buffered channel
14 compensated multi-tone signal, wherein the jitter
15 compensation module includes : a jitter compensation filter
16 with programmable filter tap weights, and means for
17 iteratively updating the filter tap weights as a function
18 of the jitter compensation filter output, wherein the means
19 for iteratively updating the filter tap weights includes a
20 signal error estimation circuit for generating from the
21 output of the jitter compensation filter a measure of a
22 symbol error; and
23 means for resetting the jitter compensation filter tap
24 weights to an initial set of values in response to the
25 control circuit determining that the output of the jitter

26 compensation filter should be used as the output of the
27 jitter compensation filter.

1 Claim 19 (currently amended): A method of processing a
2 multi-tone signal using a filter having a plurality of tap
3 weights to reduce an effect of phase jitter on a block of
4 data representing at least one transmitted symbol, the
5 method comprising the steps of:
6 performing a Fourier transform operation on the multi-
7 tone signal;
8 buffering a block of samples produced from the output
9 of said Fourier transform operation; and
10 performing a jitter compensation operation, said
11 jitter compensation operation including:
12 i) operating said a filter having a plurality of
13 tap weights to filter said block of samples to produce
14 a filtered block of data;
15 ii) determining a signal error from the filtered
16 block of data;
17 iii) updating at least one of said plurality of
18 tap weights in said filter as a function of the
19 determined signal error; and
20 iv) repeating steps i, ii, and iii until a filter
21 updating stop criterion is satisfied.

1 Claim 20 (original): The method of claim 19, further
2 comprising the step of:
3 supplying the filtered block of data output by
4 said filter when said filter updating criterion is
5 satisfied to subsequent receiver circuitry.

1 Claim 21 (original): The method of claim 19, wherein said
2 filter updating stop criterion is the completion of a fixed
3 number of filtering operations on said block of data.

1 Claim 22 (original): The method of claim 21, wherein said
2 filter updating criterion is a failure in the signal error
3 to exhibit an improvement over the previous signal error.

1 Claim 23 (original): The method of claim 19, wherein said
2 step of determining a signal error includes generating a
3 decision directed error value.

1 Claim 24 (original): The method of claim 19, wherein said
2 step of determining a signal error includes generating a
3 non-decision directed error value.

1 Claim 25 (currently amended): The method of claim 19,
2 further comprising:
3 prior to performing ~~step i~~, said buffering,
4 performing a channel compensation operation on said block
5 of data.

1 Claim 26 (original): The method of claim 25, a single
2 channel compensation operation is performed on the block of
3 data in a first period of time; and
4 step i, ii and iii are performed multiple times
5 in a time period which is equal to or shorter than the
6 first time period.